

# Victaulic® Zero-Flex™ Rigid Coupling

## Style 07



### 1.0 PRODUCT DESCRIPTION

**Available Sizes:**

- 2 – 12"/DN50 – DN300
- For sizes 14 – 24"/DN350 – DN600, please reference [publication 20.02](#): Victaulic Style W07 AGS™ Rigid Coupling

**Maximum Working Pressure:**

- Accommodates pressures ranging from full vacuum (29.9 in Hg/760 mm Hg) up to 750 psi/5171 kPa/52 bar
- Working pressure dependent on material, wall thickness and size of pipe

**Application:**

- Joins Victaulic Original Groove System (OGS) roll grooved pipe and cut grooved pipe, valves, fittings and accessories
- Provides a rigid pipe joint designed to restrict axial or angular movement. Contact Victaulic for information on torsional resistance.

**Pipe Materials:**

- Carbon steel
- For use on stainless steel pipe, please reference [publication 17.09](#): Victaulic Grooved Couplings Performance Data for Stainless Steel Pipe.

**Pipe Preparation**

- Cut or roll grooved in accordance with [publication 25.01](#): Victaulic Standard Groove Specifications

**Code Requirements:**

- Support and hanging requirements correspond to ASME B31.1 Power Piping Code, ASME B31.9 Building Services Code and NFPA 13 Sprinkler Systems

### 2.0 CERTIFICATION/LISTINGS



**NOTES**

- Download [publication 10.01](#) for Fire Protection Certifications/Listings Reference Guide.
- See [publication 02.06](#): Victaulic Potable Water Approvals ANSI/NSF for potable water approvals if applicable.

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

System No.		Location	
Submitted By		Date	

Spec Section		Paragraph	
Approved		Date	

### 3.0 SPECIFICATIONS – MATERIAL

---

**Housing:** Ductile iron conforming to ASTM A536, Grade 65-45-12. Ductile iron conforming to ASTM A395, Grade 65-45-15, is available upon special request.

**Housing Coating: (specify choice)**

Standard: Orange enamel.

Optional: Hot dipped galvanized conforming to ASTM A153.

Optional: Contact Victaulic with your requirements for other coatings.

**Gasket: (specify choice<sup>1</sup>)**

**Grade “E” EPDM**

EPDM (Green stripe color code). Temperature range –30°F to +230°F/–34°C to +110°C. May be specified for hot water service within the specified temperature range plus a variety of dilute acids, oil-free air and many chemical services. UL Classified in accordance with ANSI/NSF 61 for cold +73°F/+23°C and hot +180°F/+82°C potable water service and ANSI/NSF 372. NOT COMPATIBLE FOR USE WITH PETROLEUM SERVICES OR STEAM SERVICES.

**Grade “T” Nitrile**

Nitrile (Orange stripe color code). Temperature range -20°F to +180°F/-29°C to +82°C. May be specified for oil related services, including air with oil vapor, this gasket may be specified for temperatures rated up to +180°F/+82°C. For water related services, this gasket may be specified for temperatures rated up to +150°F/+66°C. For oil free, dry air services, this gasket may be specified for temperatures rated up to +140°F/+60°C. NOT COMPATIBLE FOR USE WITH HOT WATER SERVICES OR STEAM SERVICES

**Others**

For alternate gasket selection, reference [publication 05.01](#): Victaulic Seal Selection Guide.


<sup>1</sup> Services listed are General Service Guidelines only. It should be noted that there are services for which these gaskets are not compatible. Reference should always be made to the latest [Victaulic Seal Selection Guide](#) for specific gasket service guidelines and for a listing of services which are not compatible.


**Bolts/Nuts:**

Carbon steel oval neck track bolts meeting the mechanical property requirements of ASTM A449 (imperial) and ISO 898-1 (metric) Class 9.8 (M10-M16) and Class 8.8 (M20 and greater). Carbon steel hex nuts meeting the mechanical property requirements of ASTM A563 Grade B (imperial – heavy hex nuts) and ASTM A563M Class 9 (metric – hex nuts). Track bolts and hex nuts are zinc electroplated per ASTM B633 ZN/FE5, finish Type III (imperial) or Type II (metric).

## 4.0 DIMENSIONS

### Style 07 Zero-Flex™ Rigid Coupling




Size		Pipe End Separation <sup>2</sup>	Bolt/Nut		Dimensions			Weight
Nominal inches DN	Actual Outside Diameter inches mm	Allowable inches mm	Qty	Size inches mm	X inches mm	Y inches mm	Z inches mm	Approximate (Each) lbs kg
1 DN25	1.315 33.7	0.05 1.2	2	3/8 x 2	2.36 60	4.22 107	1.84 47	1.6 0.7
1 1/4 DN32	1.660 42.4	0.05 1.2	2	3/8 x 2	2.69 68	4.62 117	1.84 47	1.6 0.7
1 1/2 DN40	1.900 48.3	0.05 1.2	2	3/8 x 2	2.94 75	5.81 148	1.84 47	1.6 0.7
2 DN50	2.375 60.3	0.07 1.7	2	1/2 x 2 1/2	3.35 85	5.78 147	1.84 47	2.3 1.0
2 1/2	2.875 73.0	0.07 1.7	2	1/2 x 2 3/4	3.88 98	6.38 162	1.84 47	2.6 1.2
DN65	3.000 76.1	0.07 1.7	2	M12 x 70.0	4.21 107	6.61 168	1.84 47	3.6 1.6
3 DN80	3.500 88.9	0.07 1.7	2	1/2 x 2 1/2	4.54 115	6.81 173	1.84 47	3.0 1.4
4 DN100	4.500 114.3	0.16 4.1	2	1/2 x 2 3/4	5.81 148	8.21 209	2.07 53	5.3 2.4
	4.250 108.0	0.16 4.1	2	M12 x 70.0	5.56 141	7.98 203	2.07 53	5.2 2.4
	5.250 133.0	0.16 4.1	2	M16 x 82.5	6.69 170	9.60 244	2.07 53	7.4 3.4
DN125	5.500 139.7	0.16 4.1	2	M16 x 82.5	6.94 176	9.82 249	2.07 53	7.6 3.4
5	5.563 141.3	0.16 4.1	2	3/8 x 3 1/4	7.03 179	9.89 251	2.07 53	7.4 3.4
	6.250 159.0	0.16 4.1	2	M16 x 82.5	7.84 199	10.54 268	2.07 53	9.2 4.2
	6.500 165.1	0.16 4.1	2	M16 x 82.5	8.13 207	10.84 275	2.07 53	8.3 3.8
6 DN150	6.625 168.3	0.16 4.1	2	3/8 x 3 1/4	8.26 210	10.83 275	2.07 53	8.3 3.8
200A	8.515 216.3	0.19 4.8	2	M20 x 110	10.47 266	13.62 346	2.50 64	14.9 6.8
8 DN200	8.625 219.1	0.19 4.8	2	3/4 x 4 1/4	10.54 268	13.74 349	2.51 64	15.1 6.8
250A	10.528 267.4	0.13 3.3	2	M22 x 165	12.64 321	16.97 431	2.56 65	11.3 25.0
10 DN250	10.750 273.0	0.13 3.3	2	3/8 x 6 1/2	12.86 327	16.98 431	2.56 65	23.5 10.7
300A	12.539 318.5	0.13 3.3	2	M22 x 165	14.65 372	18.90 480	2.56 65	12.8 28.2
12 DN300	12.750 323.9	0.13 3.3	2	3/8 x 6 1/2	14.86 377	18.88 480	2.56 65	28.2 12.8
14 – 24 DN350 – DN600	<p><b>For sizes 14 – 24"/DN350 – DN600, please reference <a href="#">publication 20.02</a>: Victaulic Style W07 AGS™ Rigid Coupling.</b></p> 							

<sup>2</sup> The allowable pipe end separation dimension shown is for system layout purposes only. Style 07 Zero-Flex™ rigid couplings are considered rigid connections and will not accommodate expansion/contraction or angular movement of the piping system. Contact Victaulic for torsional resistance information.

## 5.0 PERFORMANCE

### Style 07 Zero-Flex™ Rigid Coupling

Size		Maximum Working Pressure <sup>3</sup>	Maximum End Load <sup>3</sup>
Nominal inches DN	Actual Outside Diameter inches mm		
1 DN25	1.315 33.7	750 5171	650 2890
1 ¼ DN32	1.660 42.4	750 5171	1620 7210
1 ½ DN40	1.900 48.3	750 5171	2130 9480
2 DN50	2.375 60.3	750 5171	3320 14775
2 ½	2.875 73.0	750 5171	4875 21695
DN65	3.000 76.1	750 5171	5300 23585
3 DN80	3.500 88.9	750 5171	7215 32105
4 DN100	4.500 114.3	750 5171	11925 53065
	4.250 108.0	750 5171	10635 47325
	5.250 133.0	700 4826	15145 67395
DN125	5.500 139.7	700 4826	16625 73980
5	5.563 141.3	750 5171	18225 81100
	6.250 159.0	700 4826	21465 95520
	6.500 165.1	700 4826	23225 103305
6 DN150	6.625 168.3	700 4826	24130 107380
200A	8.515 216.3	600 4137	34200 152200
8 DN200	8.625 219.1	600 4137	35000 155750
250A	10.528 267.4	500 3447	43500 193600
10 DN250	10.750 273.0	500 3447	45400 202030
300A	318.5 12.539	400 2758	49400 219800
12 DN300	12.750 323.9	400 2758	51000 226950
14–24 DN350–DN600	For sizes 14 – 24"/DN350 – DN600, please reference <a href="#">publication 20.02: Victaulic Style W07 AGS™ Rigid Coupling</a> . 		

<sup>3</sup> Working Pressure and End Load are total, from all internal and external loads, based on ANSI B36.10 sized carbon steel pipe, grooved in accordance with Victaulic specifications. Contact Victaulic for performance on other pipe.

**NOTE**

- WARNING: FOR ONE TIME FIELD TEST ONLY, the Maximum Joint Working Pressure may be increased to 1 ½ times the figures shown.

## 6.0 NOTIFICATIONS

### WARNING



- Read and understand all instructions before attempting to install, remove, adjust, or maintain any Victaulic piping products.
- Always verify that the piping system has been completely depressurized and drained immediately prior to installation, removal, adjustment, or maintenance of any Victaulic products.
- Wear safety glasses, hardhat, and foot protection.

Failure to follow these instructions could result in death or serious personal injury and property damage.

### WARNING

- Style 07 Zero-Flex™ Rigid Couplings shall not be used to join PVC or CPVC pipe.

Failure to follow this instruction could cause product failure, resulting in death or serious personal injury and property damage.

### WARNING

- Victaulic RX roll sets shall be used when grooving light-wall/thin-wall stainless steel pipe for use with Victaulic Couplings.

Failure to use Victaulic RX roll sets when grooving light-wall/thin-wall stainless steel pipe could cause product failure, resulting in death or serious personal injury and property damage.

### NOTICE

- Victaulic RX grooving rolls must be ordered separately. They are identified by a silver color and the designation RX on the front of the roll sets.

## 7.0 REFERENCE MATERIALS

[02.06: Victaulic Potable Water Approvals ANSI/NSF](#)

[05.01: Victaulic Seal Selection Guide - Elastomeric Seal Construction](#)

[06.17: Couplings and Fittings for JIS Pipe](#)

[10.01: Victaulic Products for Fire Protection Piping Systems - Regulatory Approval Reference Guide](#)

[17.01: Victaulic Pipe Preparation for Use on Stainless Steel Pipe with Victaulic Products](#)

[17.09: Victaulic Ductile Iron Grooved Couplings Performance Data for Stainless Steel Pipe](#)

[20.02: Victaulic AGS Rigid Coupling Style W07](#)

[26.01: Victaulic Design Data](#)

[29.01: Victaulic Terms and Conditions of Sale](#)

[I-100: Victaulic Field Installation Handbook](#)

[I-ENDCAP: Victaulic End Cap Installation Safety Instructions](#)

### User Responsibility for Product Selection and Suitability

Each user bears final responsibility for making a determination as to the suitability of Victaulic products for a particular end-use application, in accordance with industry standards and project specifications, and the applicable building codes and related regulations as well as Victaulic performance, maintenance, safety, and warning instructions. Nothing in this or any other document, nor any verbal recommendation, advice, or opinion from any Victaulic employee, shall be deemed to alter, vary, supersede, or waive any provision of Victaulic Company's standard conditions of sale, installation guide, or this disclaimer.

### Intellectual Property Rights

No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Victaulic or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right. The terms "Patented" or "Patent Pending" refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries.

### Note

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

### Installation

Reference should always be made to the Victaulic installation handbook or installation instructions of the product you are installing. Handbooks are included with each shipment of Victaulic products, providing complete installation and assembly data, and are available in PDF format on our website at [www.victaulic.com](http://www.victaulic.com).

### Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

### Trademarks

*Victaulic* and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries.