uponor

ProPEX[®] Lead-free (LF) Brass Female Threaded Adapter

Submittal Information Revision A: Jan. 20, 2010

Project Information

-		-,	_		-	 	 	
Jo	b	N	la	me	e:			

Job Name:		
Location:	Part No. Ordered:	
Engineer:	Date Submitted:	
Contractor:	Submitted By:	
Manufacturer's Representative:	Approved By:	


Technical Data

Material:

C69300 Brass

Product Information and Application Use

The ProPEX[®] Lead-free Brass Female Threaded Adapter connects Uponor PEX tubing to female NPT threads.¹ Use these fittings in hot and cold domestic potable water systems or in any radiant heating system. One end of the adapter is manufactured with the Uponor ProPEX Fitting for connections to Wirsbo hePEX[™] tubing or Uponor AquaPEX[®] tubing. The other end of the adapter connects to copper. These adapters are safe for direct burial in soil.



✓	Description	Part Number	Α	В	С	Weight
	ProPEX LF Brass Female Threaded Adapter, $\frac{1}{2}$ " PEX x $\frac{1}{2}$ " NPT	LF4575050	1.57"	1" HEX	1⁄2" NPT	0.20 lbs.
	ProPEX LF Brass Female Threaded Adapter, $\frac{1}{2}$ " PEX x $\frac{3}{4}$ " NPT	LF4575075	1.75"	1³/16" HEX	34" NPT	0.40 lbs.
	ProPEX LF Brass Female Threaded Adapter, 34 " PEX x 34 " NPT*	LF4577575	1.87"	1%" HEX	34" NPT	0.20 lbs.
	ProPEX LF Brass Female Threaded Adapter, 34 " PEX x 1" NPT	LF4577510	2.21"	11⁄2" HEX	1" NPT	0.40 lbs.
	ProPEX LF Brass Female Threaded Adapter, 1" PEX x 1" NPT	LF4571010	2.44"	11⁄2" HEX	1" NPT	0.45 lbs.
	ProPEX LF Brass Female Threaded Adapter, 14 " PEX x 14 " NPT	LF4571313	2.57"	2" HEX	1¼" NPT	1.00 lbs.
	ProPEX LF Brass Female Threaded Adapter, $1\frac{1}{2}$ " PEX x $1\frac{1}{2}$ " NPT	LF4571515	2.75"	21⁄2" HEX	11⁄2" NPT	2.20 lbs.
	ProPEX Brass Female Threaded Adapter, 2" PEX x 2" NPT	LF4572020	3.53"	3" HEX	2" NPT	2.20 lbs.

Installation

ProPEX Tool and ProPEX Rings (sold separately) are required for connecting the PEX tubing. For more information, refer to the AquaPEX Professional Plumbing Installation Guide or the Radiant Floor Heating Installation Handbook.

Standards

CAN/CSA B137.5; ASTM F877; ASTM F1960

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

ANSI/NSF 14- and 61-certified; ICC ESR 1099; HUD MR 1269; U.P. Code, Annex G; *UL 1821; *ULC/ORD C199P

Related Applications

PEX-a Plumbing Systems Radiant Heating and Cooling Systems Snow and Ice Melting Systems Permafrost Protection Systems Turf Conditioning Systems

Contact Information

Uponor, Inc. 5925 148th Street West Apple Valley, MN 55124 USA Phone: (800) 321-4739 Fax: (952) 891-1409 www.uponor-usa.com Uponor Ltd. 2000 Argentia Rd., Plaza 1, Ste. 200 Mississauga, ON L5N 1W1 CANADA Phone: (888) 994-7726 Fax: (800) 638-9517 www.uponor.ca