

Case and ring options	Code	Comments
Hermetically Sealed or Weatherproof Liquid-Fillable Case	LJ	Gauge furnished dry or for liquid filling. Includes a solid fill plug and throttle plug for ranges 30 psi and above.
U-Clamp	UC	Used for panel mounting back-connect gauges.
Front Flange	FF	Includes 3 holes for panel mounting gauges. (back-connect only)
Wall Mounting Bracket	BF	Available on 4½" 1009 lower or back-connect.
Back Flange for Wall Mounting	FW	Available on 2½" and 3½" 1009 lower or back-connect.
Retrofit Flange	RF	Available on 63mm and 100mm 1008 back-connect gauges for panel mounting. (Includes U-clamp.)
Metric Gauge	MG	Available on 3½" 1009 with ½ NPT lower connection. Gauge supplied with micrometer pointer, white dial and safety glass.
Bourdon tube and system assembly options		
SS Throttle Plug – (restrictor) Push-in Design	TU	SS push-in type with a 0.013" orifice for 2½", 3½", 100mm 1009, 63mm, 100mm 1008. Throttle plug standard on all 2½", 3½" 1009, 40mm thru 100mm 1008 liquid filled gauges 30 psi—1000 psi
SS Throttle Plug (restrictor) Helical Design	TS	Standard on all 2½", 3½", 100mm 1009s, 40mm, thru 100mm 1008 liquid filled gauges with ranges of 1500 psi and above. 4½", 6" 1009 furnished with thread-in design with a .031" orifice.
Liquid Filled Gauge Without Throttle Plug	WP	Required when the process may clog a throttle plug on the gauge.
Cleaning for Gaseous Oxygen	6B	If gauge is liquid filled specify Halocarbon as the fill.
Liquid filling options		
Silicone Fill	GV	Not available on 40mm and 50mm 1008 gauges.
Halocarbon Fill	GX	Not available on 40mm and 50mm 1008. For oxidizing media. Examples: chlorine, oxygen, nitric acid and sulfuric acid.
Pointer options		
Red Set-Hand (Single)	SH	Available on 1009 only. Single stationary set-hand used to indicate a specific pressure.
Red Set-Hand (Double)	SJ	Available on 1009 only. Double stationary set-hand used to indicate 2 specific pressures.
Red Set-Hand (Adjustable)	EU	Available on 1009 only.
Maximum Pointer	EP	Available on 4½" and 6" 1009 only. Externally reset by a knob on outside of an acrylic window.
Minimum Pointer	EQ	Available on 4½" and 6" 1009 only. Externally reset by a knob on outside of an acrylic window.
Window options		
Polycarbonate Window	PD	40mm, 50mm 1008 only. Ambient temperature limits -50/270°F. XPD standard on 2½", 3½" 1009 and 63mm and 100mm 1008.
Acrylic Window	PD	4½" and 6" 1009 only. Ambient temperature limits -50/180°F.
Shatterproof Glass	SG	Not available on 63mm, 100mm 1008. Ambient temperature limits -50/200°F.
External Zero Adjustable Pointer (Easy Zero™)	EA	Available in 3½" 1009 only dry or liquid filled.
Marking and tagging options		
Dial Marking	DA	Service marking printed on dial.
Paper Tagging of Carton and Gauge	NN	Tag is bonded to gauge case and carton.
Stainless Steel Tagging of Gauge Case	NH	300 series stainless steel tag is wired to gauge case.
Calibration options		
Accuracy 0.5% full scale	AN	4½" and 6" 1009 only.
Test and certificate options		
Certificate of Conformance	CD-1	Conformance to specifications and/or drawings.
Individual Certified Calibration Chart	CD-4	
Special connection options		
½" NPT	01	Available on 2½", 3½" 1009SW.
SAE ⅞" and 20 straight thread	RW	Not available on 40mm, 50mm 1008
⅞" and 20 UNF-3A 37° Flare	EJ	Not available on 40mm, 50mm 1008
¼" straight JIS, BSP	KJ	Not available on 40mm, 50mm 1008
¼" tapered JIS, BSP	KA	Not available on 40mm, 50mm 1008
⅜" straight JIS, BSP	KP	3½", 100mm 1009SW lower connection only
½" straight JIS, BSP	KN	3½", 100mm 1009SW lower connection only
⅜" tapered JIS, BSP	KR	3½", 100mm 1009SW lower connection only
½" tapered JIS, BSP	KQ	3½", 100mm 1009SW lower connection only
G ¼" DIN	13	Not available on 40mm, 50mm 1008