

WATER PRO


Precharged Water System Tanks





WATER PRO

Water Pro precharged well tanks deliver reliable performance at an affordable price. All feature Stainless Steel connection, 125 PSI working pressure, Fresh Water Turbulator™ and a 5-year limited warranty. Water Pro tanks are Made in the USA at our ISO 9001:2008 registered facilities.



| Specifications | | | | | | | | | | | | |
|-----------------|-----------------------------|--|--------------------|--------------------|--------------------|---------------------------|-------------------------|----------------------|-----------------|---------|--|--|
| Model Number | Tank Volume (Gallons) | Max. Accept. Volume (Gallons) | System Drawdown | | | Dimensions | | System | Shipping Weight | | | |
| | | | 20/40 (Gallons) | 30/50 (Gallons) | 40/60 (Gallons) | A Diameter (Inches) | B Height (Inches) | Connection (NPTF) | Lbs. | Cu. Ft. | | |
| WP20SS | 20.0 | 0.57 | 8.0 | 6.8 | 5.9 | 15 % | 31 % | 1 | 28 | 4.9 | | |
| WP26SS | 26.0 | 0.44 | 10.5 | 8.8 | 7.6 | 15 % | 38 1/4 | 1 | 34 | 5.2 | | |
| WP32SS | 32.0 | 0.35 | - | 10.9 | 9.4 | 15 % | 46 ½ | 1 | 40 | 7.0 | | |
| WP44SS | 44.0 | 0.77 | 17.7 | 15.0 | 12.9 | 22 | 36 | 1 | 57 | 11.0 | | |
| WP62SS | 62.0 | 0.55 | 24.9 | 21.1 | 18.2 | 22 | 46 ¾ | 1 1/4 | 75 | 13.9 | | |
| WP81SS | 81.0 | 0.41 | 32.6 | 27.5 | 23.8 | 22 | 56 ¾ | 1 1/4 | 92 | 15.8 | | |
| WP86SS | 86.0 | 0.54 | 34.6 | 29.2 | 25.3 | 26 | 47 1/4 | 1 1/4 | 99 | 18.9 | | |
| WP119SS | 119.0 | 0.39 | 47.8 | 40.5 | 35.0 | 26 | 61 1/8 | 1 1/4 | 133 | 24.5 | | |

Maximum Operating Temperature: 200°F. Factory Precharge: 38 PSI.



| PUMP FLOW RATE | Minimu | Minute Ru m Running Time t I HP & Smaller Pu | o Protect | Two Minute Runtime For Larger Pumps and More Economic Operation | | | | |
|----------------------|---------|--|------------|---|-------------|------------|--|--|
| (GPM) | 20/40 | 30/50 | 40/60 | 20/40 | 30/50 | 40/60 | | |
| 5 | WP20SS | WP20SS | WP20SS | WP26SS | WP32SS | WP32SS | | |
| 7 | WP20SS | WP20SS | WP26SS | WP32SS | WP44SS | WP62SS | | |
| 10 | WP26SS | WP32SS | WP44SS | WP62SS | WP62SS | WP81SS | | |
| 12 | WP32SS | WP44SS | WP44SS | WP62SS | WP81SS | WP81SS | | |
| 15 | WP44SS | WP44SS | WP62SS | WP81SS | WP86SS | WP119SS | | |
| 20 | WP62SS | WP62SS | WP81SS | WP119SS | WP119SS | (2) WP81SS | | |
| 25 | WP62SS | WP81SS | WP86SS | (2) WP62SS | (2) WP81SS | (2) WP86SS | | |
| 30 | WP81SS | WP86SS | WP119SS | (2) WP81SS | (2) WP86SS | (2)WP119SS | | |
| 35 | WP86SS | WP119SS | WP119SS | (2) WP86SS | (2) WP119SS | (2)WP119SS | | |
| 40 | WP119SS | WP119SS | (2) WP81SS | (2) WP119SS | (2) WP119SS | (2) WP86SS | | |











1400 Division Road, West Warwick, RI 02893 USA T: 800.426.8765 F: 800.293.1519 www.amtrol.com