

PLASTIC PIPE CEMENTS, PRIMERS & CLEANERS cont'd

wet set pvc cement

aqua blue, medium body, fast set

For PVC Types I & II, potable water, DWV, and SW pipe and fittings up to 8" diameter, Schedules 40 and 80. NSF and UPC listed. Formulated for applications where conditions are very wet and/or when quick pressurization is imperative. Ideal for lawn sprinkler and swimming pool installations. Conforms to ASTM D2564.

½ pt., 1 pt., 1 qt., 1 gal.

cpvc cement

orange, medium body, fast set

For ASTM D1784, Class 23447B, CPVC potable water pipe and fittings up to 8" diameter all Schedules. NSF and UPC listed. Conforms to ASTM F493.

¼ pt., ½ pt., 1 pt., 1 qt.

cpvc gold

gold, medium body, medium set

One step, low V.O.C. cement for use on ALL CPVC pipe and fittings including FlowGuard Gold™*, CPVC potable water, SDR-PR CPVC pipe fittings up to 6" diameter Schedules 40 and 80. NSF and UPC listed. Conforms to ASTM D-2846 and F-493.

¼ pt., ½ pt., 1 pt., 1 qt.

*Trademark of The BFGoodrich Co.

primer for pvc and cpvc

purple

Recommended method to soften and prepare surface of PVC and CPVC pipe and fittings (all sizes and Schedules except copper tube size CPVC) before applying solvent cements. NSF and UPC listed. Conforms to ASTM D656.

¼ pt., ½ pt., 1 pt., 1 qt., 1 gal.

pvc primer

clear

Recommended method to soften and prepare surface of PVC pipe and fittings (all sizes and Schedules) before applying solvent cements. NSF listed. Conforms to ASTM F656.

¼ pt., ½ pt., 1 pt., 1 qt., 1 gal.

pvc primer

purple

Recommended method to soften and prepare surface of PVC pipe and fittings (all sizes and Schedules) before applying solvent cements. NSF and UPC listed. Conforms to ASTM F656.

¼ pt., ½ pt., 1 pt., 1 qt., 1 gal.

abs cement

black, medium body, fast set

For ABS potable water, DWV and SW pipe and fittings up to 8" diameter all Schedules. NSF and UPC listed. Conforms to ASTM D2235.

¼ pt., ½ pt., 1 pt., 1 qt., 1 gal.

abs/pvc transition cement

green, medium body, fast set

For joining ABS to PVC pipe or fittings up to 6" diameter all Schedules. NSF and UPC listed. Conforms to ASTM D3138.

½ pt., 1 pt.

multi-purpose cement

milky, medium body, fast set

For joining PVC, CPVC and ABS pipe and fittings up to 6" diameter Schedule 40. Conforms to ASTM F493 and ASTM D2846.

¼ pt., ½ pt., 1 pt., 1 qt., 1 gal.

plastic pipe & fittings cleaner clear

For removing foreign matter and dirt from ABS, PVC, CPVC, and Styrene pipe and fittings surfaces.

¼ pt., ½ pt., 1 pt., 1 qt., 1 gal.

Low VOC products are available for use
where required by local regulation.