



#017566-144

PTFE Pipe Tape

PurePro® Pipe Tape is the ideal solution for sealing threaded pipe connections up to 2" diameter. PurePro Pipe Tape provides a tight seal while providing natural lubrication to prevent damage of the threads. Made of 100% PTFE, it is resistant to wmost common chemicals, and is rated for temperatures from -450° F to +500° F. Available in widths of 1/2", 3/4" and 1", PurePro Pipe Tape can be used with applications involving water, steam, air, oils, and most common chemicals.

General:

- Composition: 100% PTFE (Polytetrafluoroethylene)
- Color: White
- Widths: 1/2", 3/4", and 1"

Specifications:

- Density: 0.5 – 0.7 g/cc
- Thickness: 0.003 min
- Pressure rating: Full vacuum to 2,000 psi
- Temperature range: -450°F to 500°F
- pH Range: 0 - 14
- Specifications:
 - Military: MIL-SPEC-T27730A
 - FDA: 21CFR177.1550
- Maximum pipe size: 2"

Other Properties:

- No age deterioration
- Non-toxic
- Non-absorbent
- Non-flammable
- Self-lubricating
- Unlimited shelf life

Country of Manufacture: USA

Specifications	
Webb#	Description
PRO017526-144	White Teflon Thread Seal Tape 1/2" x 520'
PRO017566-144	White Teflon Thread Seal Tape 3/4" x 520'
PRO017588-144	White Teflon Thread Seal Tape 1" x 520'