

SUBMITTAL SHEET

| | |
|------------------------|--|
| Job Name: | |
| Job Location: | |
| Engineer: | |
| Contractor: | |
| Tag: | |
| PO Number: | |
| Representative: | |
| Wholesale Distributor: | |

Frost-Free Sillcocks Specifications

Material Specifications

- Body: Lead free Brass, chrome plated
- Outer Tube: Lead free Brass, chrome plated
- End Adapter: Lead free Brass, chrome plated
- Bonnet Nut Assembly: Forged Brass chrome plated
- Handle: Aluminum TPR coated
- Stem: Lead free brass/ Other materials
- Vacuum Breaker Assembly: POM (High performance thermoplastic)



Technical Specifications

- Maximum operating pressure: 125 PSI water
- Operating temperature: 32°F to 140°F
- Outlet connection: 3/4 hose thread

Certifications

- ASSE 1019-A - Meets performance requirements for wall hydrant with backflow protection and freeze resistance.



1/4 Turn Frost-Free Sillcocks

| Specifications | | | |
|---------------------------|---------|-----------------|--|
| Category | Webb # | Mfr. # | Description |
| 1/4 TURN PRESS | 1279230 | PROFPSQTPRS6LF | FROSTFREE SLCOK 1/4TURN LF BRS 1/2x6" PRS |
| 1/4 TURN PRESS | 1279229 | PROFPSQTPRS8LF | FROSTFREE SLCOK 1/4TURN LF BRS 1/2x8" PRS |
| 1/4 TURN PRESS | 1279228 | PROFPSQTPRS10LF | FROSTFREE SLCOK 1/4TURN LF BRS 1/2x10" PRS |
| 1/4 TURN PRESS | 1279232 | PROFPSQTPRS12LF | FROSTFREE SLCOK 1/4TURN LF BRS 1/2x12" PRS |
| 1/4 TURN PRESS | 1279231 | PROFPSQTPRS14LF | FROSTFREE SLCOK 1/4TURN LF BRS 1/2x14" PRS |
| 1/4 TURN THREADED / SWEAT | 1279224 | PROFPSQT6LF | FROSTFREE SLCOK 1/4TURN LF 1/2x6" THD SWT |
| 1/4 TURN THREADED / SWEAT | 1279226 | PROFPSQT8LF | FROSTFREE SLCOK 1/4TURN LF 1/2x8" THD SWT |
| 1/4 TURN THREADED / SWEAT | 1279222 | PROFPSQT10LF | FROSTFREE SLCOK 1/4TURN LF 1/2x10" THD SWT |
| 1/4 TURN THREADED / SWEAT | 1279223 | PROFPSQT12LF | FROSTFREE SLCOK 1/4TURN LF 1/2x12" THD SWT |
| 1/4 TURN THREADED / SWEAT | 1279225 | PROFPSQT14LF | FROSTFREE SLCOK 1/4TURN LF 1/2x14" THD SWT |

SUBMITTAL SHEET

| | |
|-------------------------------|--|
| Job Name: | |
| Job Location: | |
| Engineer: | |
| Contractor: | |
| Tag: | |
| PO Number: | |
| Representative: | |
| Wholesale Distributor: | |



1/4 Turn Frost-Free Sillcocks

| DIM. | ITEM NO. | | SIZE | UNIT | PER CTMR DWG | DATE | REV. | |
|------|--------------|-----------------|-----------|-----------------|--------------|------------|------|--|
| L | | | A4 | INCH | XXX | XX-XX-XX | X | |
| 6" | PROFPSQT6LF | PROFPSQTPRS6LF | REVISIONS | | | | | |
| 8" | PROFPSQT8LF | PROFPSQTPRS8LF | REV. | DESCRIPTION | APR. | DATE | | |
| 10" | PROFPSQT10LF | PROFPSQTPRS10LF | A | Initial Release | UPE | 2025/11/21 | | |
| 12" | PROFPSQT12LF | PROFPSQTPRS12LF | | | | | | |
| 14" | PROFPSQT14LF | PROFPSQTPRS14LF | | | | | | |

| NO. | DESCRIPTION | MATERIAL | QTY |
|-----|-------------|------------------|-----|
| 1 | SCREW | BRASS | 1 |
| 2 | NAME DISC | ALUMINUM | 1 |
| 3 | HANDLE | TPR/ALUMINUM | 1 |
| 4 | NUT | BRASS(C46400) | 1 |
| 5 | O-RING | RUBBER | 1 |
| 6 | NUT | BRASS(C3604) | 1 |
| 7 | WASHER | RUBBER | 1 |
| 8 | STEM | BRASS(C27000) | 1 |
| 9 | SET SCREW | S.S | 1 |
| 10 | WASHER | RUBBER | 1 |
| 11 | CARTRIDGE | BRASS(C46400) | 1 |
| 12 | O-RING | RUBBER | 2 |
| 13 | VALVE BODY | BRASS(C6802 MOD) | 1 |
| 14 | VB COVER | PLASTIC | 1 |
| 15 | VB BODY | PLASTIC | 1 |
| 16 | VB STEM | PLASTIC | 1 |
| 17 | O-RING | RUBBER | 1 |
| 18 | SEAT | RUBBER | 1 |
| 19 | ADAPTER | BRASS(C46400) | 1 |
| 20 | TUBE | BRASS(C27000) | 1 |
| 21 | INSERT | PLASTIC | 1 |

| ITEM NO. | ADAPTER |
|----------------|---------|
| PROFPSQTxLF | |
| PROFPSQTPRSxLF | |

| | | | |
|---|---------------------|---|-------------------------|
| DO NOT SCALE DRAWING | | C.S.B. INTERNATIONAL PRODUCTS INC. | |
| TOLERANCES : UNLESS OTHERWISE SPECIFIED . XX ± 0.010 ANGLES ± 1/2° . XXX ± 0.005 FRACTION ± 1/64 | | TITLE FROSTFREE SLCOK 1/4 TURN | DRAWN Makey 11/21/25 |
| W.T.: | MATERIAL : SEE LIST | ITEM No. | SCALE PROJECTION |
| FINISH : | | REV. A | FREE FILE XXX |
| | | SHEET : 1 / 1 | FILE XXX |

SUBMITTAL SHEET

Frost-Free Sillcocks Specifications

Material Specifications

- Body: Lead free Brass, chrome plated
- Outer Tube: Lead free Brass, chrome plated
- End Adapter: Lead free Brass, chrome plated
- Bonnet Nut Assembly: Forged Brass chrome plated
- Handle: Aluminum TPR coated
- Stem: Lead free brass/ Other materials
- Vacuum Breaker Assembly: POM (High performance thermoplastic)

Technical Specifications

- Maximum operating pressure: 125 PSI water
- Operating temperature: 32°F to 140°F
- Outlet connection: 3/4 hose thread

Certifications

- ASSE 1019-A - Meets performance requirements for wall hydrant with backflow protection and freeze resistance.

| | |
|-------------------------------|--|
| Job Name: | |
| Job Location: | |
| Engineer: | |
| Contractor: | |
| Tag: | |
| PO Number: | |
| Representative: | |
| Wholesale Distributor: | |



PROFPSMTPRS6LF



PROFPSMTPXB6LF



PROFPSMTPXA6LF



PROFPSQT6LF



CUSTOMER SERVICE: ph: 888-936-0880
 email: purepro@fwwebb.com
fwwebb.com/purepro

Multi Turn Frost-Free Sillcocks

| Specifications | | | |
|-----------------------------|---------|-----------------|---|
| Category | Webb # | Mfr. # | Description |
| MULTI-TURN PRESS | 1279211 | PROFPSMTPRS6LF | FROSTFREE SLCOK MTURN LF BRS 1/2x6" PRS |
| MULTI-TURN PRESS | 1279212 | PROFPSMTPRS8LF | FROSTFREE SLCOK MTURN LF BRS 1/2x8" PRS |
| MULTI-TURN PRESS | 1279209 | PROFPSMTPRS10LF | FROSTFREE SLCOK MTURN LF BRS 1/2x10" PRS |
| MULTI-TURN PRESS | 1279210 | PROFPSMTPRS12LF | FROSTFREE SLCOK MTURN LF BRS 1/2x12" PRS |
| MULTI-TURN THREADED / SWEAT | 1279206 | PROFPSMT4LF | FROSTFREE SLCOK MTURN LF 1/2x4" THD SWT |
| MULTI-TURN THREADED / SWEAT | 1279207 | PROFPSMT6LF | FROSTFREE SLCOK MTURN LF 1/2x6" THD SWT |
| MULTI-TURN THREADED / SWEAT | 1279208 | PROFPSMT8LF | FROSTFREE SLCOK MTURN LF 1/2x8" THD SWT |
| MULTI-TURN THREADED / SWEAT | 1279204 | PROFPSMT10LF | FROSTFREE SLCOK MTURN LF 1/2x10" THD SWT |
| MULTI-TURN THREADED / SWEAT | 1279205 | PROFPSMT12LF | FROSTFREE SLCOK MTURN LF 1/2x12" THD SWT |
| MULTI-TURN THREADED / SWEAT | 1279206 | PROFPSMT4LF | FROSTFREE SLCOK MTURN LF 1/2x4" THD SWT |
| MULTI-TURN PEX CRIMP | 1279219 | PROFPSMTPXB6LF | FROSTFREE SLCOK MTURN LF 1/2x6" PEX CRMP |
| MULTI-TURN PEX CRIMP | 1279220 | PROFPSMTPXB8LF | FROSTFREE SLCOK MTURN LF 1/2x8" PEX CRMP |
| MULTI-TURN PEX CRIMP | 1279217 | PROFPSMTPXB10LF | FROSTFREE SLCOK MTURN LF 1/2x10" PEX CRMP |
| MULTI-TURN PEX CRIMP | 1279218 | PROFPSMTPXB12LF | FROSTFREE SLCOK MTURN LF 1/2x12" PEX CRMP |
| MULTI-TURN THREADED / SWEAT | 1279206 | PROFPSMT4LF | FROSTFREE SLCOK MTURN LF 1/2x4" THD SWT |
| MULTI-TURN PEX EXPANSION | 1279215 | PROFPSMTPXA6LF | FROSTFREE SLCOK MTURN LF 1/2x6" PEX EXP |
| MULTI-TURN PEX EXPANSION | 1279216 | PROFPSMTPXA8LF | FROSTFREE SLCOK MTURN LF 1/2x8" PEX EXP |
| MULTI-TURN PEX EXPANSION | 1279213 | PROFPSMTPXA10LF | FROSTFREE SLCOK MTURN LF 1/2x10" PEX EXP |
| MULTI-TURN PEX EXPANSION | 1279214 | PROFPSMTPXA12LF | FROSTFREE SLCOK MTURN LF 1/2x12" PEX EXP |

SUBMITTAL SHEET

| | |
|-------------------------------|--|
| Job Name: | |
| Job Location: | |
| Engineer: | |
| Contractor: | |
| Tag: | |
| PO Number: | |
| Representative: | |
| Wholesale Distributor: | |



PROFPSMTPRS6LF



PROFPSMTPXB6LF



PROFPSMTPXA6LF



PROFPSQT6LF

Multi Turn Frost-Free Sillcocks

| DIM. L | ITEM NO. | | | | SIZE | UNIT | PER CTMR DWG | DATE | REV. |
|--------|--------------|-----------------|-----------------|-----------------|-----------|-----------------|--------------|----------|------------|
| 4" | PROFPSMT4LF | | | | A4 | INCH | XXX | XX-XX-XX | X |
| 6" | PROFPSMT6LF | PROFPSMTPRS6LF | PROFPSMTPXB6LF | PROFPSMTPXA6LF | REVISIONS | | | | |
| 8" | PROFPSMT8LF | PROFPSMTPRS8LF | PROFPSMTPXB8LF | PROFPSMTPXA8LF | REV. | DESCRIPTION | | APR. | DATE |
| 10" | PROFPSMT10LF | PROFPSMTPRS10LF | PROFPSMTPXB10LF | PROFPSMTPXA10LF | A | Initial Release | | UPE | 2025/11/21 |
| 12" | PROFPSMT12LF | PROFPSMTPRS12LF | PROFPSMTPXB12LF | PROFPSMTPXA12LF | | | | | |

| ITEM NO. | ADAPTER |
|----------------|---------|
| PROFPSMTxLF | |
| PROFPSMTPBxLF | |
| PROFPSMTPAxLF | |
| PROFPSMTPRSxLF | |

| NO. | DESCRIPTION | MATERIAL | QTY |
|-----|-------------|------------------|-----|
| 1 | HANDLE | TPR/ALUMINUM | 1 |
| 2 | SCREW | BRASS(C26000) | 1 |
| 3 | STEM HOLDER | BRASS(C3604) | 1 |
| 4 | WASHER | S.S.304 | 1 |
| 5 | PACKING | RUBBER | 1 |
| 6 | WASHER | S.S.304 | 1 |
| 7 | VALVE BODY | BRASS(C8802 MOD) | 1 |
| 8 | PACKING | RUBBER | 1 |
| 9 | PLUNGER | PLASTIC | 1 |
| 10 | ADAPTER | PLASTIC | 1 |
| 11 | VB COVER | PLASTIC | 1 |
| 12 | O-RING | RUBBER | 1 |
| 13 | TUBE | BRASS(C27000) | 1 |
| 14 | STEM | BRASS(C27000) | 1 |
| 15 | CONNECTOR | BRASS(C46400) | 1 |
| 16 | SPRING | S.S.304 | 1 |
| 17 | PLINGER | BRASS(C46400) | 1 |
| 18 | O-RNG | RUBBER | 1 |
| 19 | PACKING | RUBBER | 1 |
| 20 | WASHER | BRASS(C26000) | 1 |
| 21 | SEAL | RUBBER | 1 |
| 22 | SCREW | BRASS(C26000) | 1 |
| 23 | ADAPTER | BRASS(C46400) | 1 |
| 24 | NAME DISC | ALUMINUM | 1 |
| 25 | INSERT | PLASTIC | 1 |

| | | | |
|---|----------|---|-------------------------|
| DO NOT SCALE DRAWING | | C.S.B. INTERNATIONAL PRODUCTS INC. | |
| TOLERANCES : UNLESS OTHERWISE SPECIFIED . XX ± 0.010 ANGLES ± 1/2° . XXX ± 0.005 FRACTION ± 1/64 | | TITLE FROSTFREE SLCOK MTURN | DRAWN Makey 11/21/25 |
| W.T.: | ITEM No. | REV. A | APR. PROJECTION |
| MATERIAL : SEE LIST | | FREE | SCALE |
| FINISH : | | SHEET : 1 / 1 | FILE XXX |