

Cleanable Standard Housing & Cartridge Options



125 psi – 8.6 BAR
pH: 6.5 – 9.5
Heavy duty 100% reinforced Polypropylene



Cleanable Housings							
Webb #	Mfr. #	Material	Flow Rate*	Connection	Cartridge Diameter	Cartridge Length	Working Temperature
1196221	PROSEDSTDILF	100% PET, FDA Grade Clear Sump	Up to 20GPM 1-4 Bathrooms	1" Lead-Free Brass FNPT	2.5"	*	39°F – 113°F
1280347	PROSCTIB-10	100% PET, FDA Grade Clear Sump	Up to 12GPM 1-2.5 Bathrooms	3/4" Lead-Free Brass FNPT	2.5"	10"	39°F – 113°F



Cartridge Choices							
Webb #	Mfr. #	Material	Treats	Micron	Cartridge Diameter	Cartridge Length	Working Temperature
1115104	PROCRBSTD-10	Carbon Block	Chlorine, Taste & Odors	5	2.5"	10"	39°F – 125°F
1196244	PROSCLSTD5MIC-10	Melt Blown Polyphosphate	Hard Water Scale Reduction	5	2.5"	10"	39°F – 177°F
480982	PROMLTBLSTD5MIC-10	Melt Blown – Grooved	Particulate & Sediment	5	2.5"	10"	39°F – 176°F
480994	PROSTGSTD5MIC-10	String Wound	Heavy Particulate & Sediment	5	2.5"	10"	39°F – 113°F
1061884	PROSTGSTD25MIC-10	String Wound	Heavy Particulate & Sediment	25	2.5"	10"	39°F – 113°F
1061938	PROSTGSTD50MIC-10	String Wound	Heavy Particulate & Sediment	50	2.5"	10"	39°F – 113°F



Accessories							
Webb #	Mfr. #	Material	Treats	Connection	Cartridge Diameter	Cartridge Length	Working Temperature
1280348	PROSTDFV	ABS		1/2" BSP			30°F – 113°F
1196222	PROSEDSTD90MIC	Stainless Steel Mesh	Particulate & Sediment	90	2.5"	*	39°F – 113°F



Misc. Accessories		
Webb #	Mfr. #	Description
1115094	PROORNGSTD	O-Ring for Standard Housings
1115093	PROWRENCHSTD	Wrench for Standard Housings
1061937	PROSTDBRK	Bracket for Standard Housings

*Flow rates based on a clean cartridge element and under normal operating conditions, we always recommend a water test to ensure proper performance.

Standard 10" Housings & Cartridge Options



125 psi - 8.6 BAR
pH: 6.5 - 9.5
Heavy duty 100% reinforced Polypropylene



Standard 10" Housings							
Webb #	Mfr. #	Material	Flow Rate*	Connection	Cartridge Diameter	Cartridge Length	Working Temperature
1196226	PROSTDCLR34LF-10	100% PET, FDA Grade Clear Sump	Up to 12GPM 1-2.5 Bathrooms	3/4" Lead-Free Brass FNPT	2.5"	10"	39°F - 113°F
1061929	PROSTDCLR34-10	100% PET, FDA Grade Clear Sump	Up to 12GPM 1-2.5 Bathrooms	3/4" FNPT	2.5"	10"	39°F - 113°F
1280345	PROSB34B-10	100% PET, FDA Grade Blue Sump	Up to 12GPM 1-2.5 Bathrooms	3/4" Lead-Free Brass FNPT	2.5"	10"	39°F - 113°F
1109869	PROSTDBLU34-10	100% PET, FDA Grade Blue Sump	Up to 12GPM 1-2.5 Bathrooms	3/4" FNPT	2.5"	10"	39°F - 113°F



Cartridge Choices							
Webb #	Mfr. #	Material	Treats	Micron	Cartridge Diameter	Cartridge Length	Working Temperature
1115104	PROCRBSTD-10	Carbon Block	Chlorine, Taste & Odors	5	2.5"	10"	39°F - 125°F
1196244	PROSCLSTD5MIC-10	Melt Blown Polyphosphate	Hard Water Scale Reduction	5	2.5"	10"	39°F - 177°F
480982	PROMTLBLSTD5MIC-10	Melt Blown - Grooved	Particulate & Sediment	5	2.5"	10"	39°F - 176°F
480994	PROTGSTD5MIC-10	String Wound	Heavy Particulate & Sediment	5	2.5"	10"	39°F - 113°F
1061884	PROTGSTD25MIC-10	String Wound	Heavy Particulate & Sediment	25	2.5"	10"	39°F - 113°F
1061938	PROTGSTD50MIC-10	String Wound	Heavy Particulate & Sediment	50	2.5"	10"	39°F - 113°F



Misc. Accessories		
Webb #	Mfr. #	Description
1115094	PROORNGSTD	O-Ring for Standard Housings
1115093	PROWRENCHSTD	Wrench for Standard Housings
1061937	PROSTDBRK	Bracket for Standard Housings

*Flow rates based on a clean cartridge element and under normal operating conditions, we always recommend a water test to ensure proper performance.

Standard 20" Housings & Cartridge Options



125 psi - 8.6 BAR
pH: 6.5 - 9.5
Heavy duty 100% reinforced Polypropylene



Complete Kit							
Webb #	Mfr. #	Material	Flow Rate*	Connection	Cartridge Diameter	Cartridge Length	Working Temperature
1196229	PROSTDCL34SS-20	100% PET, FDA Grade Clear Sump	Up to 16GPM 1-3 Bathrooms	3/4" Lead-Free Brass FNPT	2.5"	20"	39°F - 113°F

Standard 20" Housings							
Webb #	Mfr. #	Material	Flow Rate*	Connection	Cartridge Diameter	Cartridge Length	Working Temperature
1196218	PROSTDCL34LF-20	100% PET, FDA Grade Clear Sump	Up to 16GPM 1-3 Bathrooms	3/4" Lead-Free Brass FNPT	2.5"	20"	39°F - 113°F
1061870	PROSTDCL34-20	100% PET, FDA Grade Clear Sump	Up to 16GPM 1-3 Bathrooms	3/4" FNPT	2.5"	20"	39°F - 113°F
1280346	PROSB34B-20	100% PET, FDA Grade Blue Sump	Up to 16GPM 1-3 Bathrooms	3/4" Lead-Free Brass FNPT	2.5"	20"	39°F - 113°F
1109870	PROSTDBLU34-20	100% PET, FDA Grade Blue Sump	Up to 16GPM 1-3 Bathrooms	3/4" FNPT	2.5"	20"	39°F - 113°F

Cartridge Choices							
Webb #	Mfr. #	Material	Treats	Micron	Cartridge Diameter	Cartridge Length	Working Temperature
1061855	PROCRBSTD-20	Carbon Block	Chlorine, Taste & Odors	5	2.5"	20"	39°F - 125°F
1196243	PROSCLSTD5MIC-20	Melt Blown Polyphosphate	Hard Water Scale Reduction	5	2.5"	20"	39°F - 177°F
480985	PROMTLBLSTD5MIC-20	Melt Blown - Grooved	Particulate & Sediment	5	2.5"	20"	39°F - 176°F
480997	PROTGSTD5MIC-20	String Wound	Heavy Particulate & Sediment	5	2.5"	20"	39°F - 113°F
1061912	PROTGSTD25MIC-20	String Wound	Heavy Particulate & Sediment	25	2.5"	20"	39°F - 113°F
1061877	PROTGSTD50MIC-20	String Wound	Heavy Particulate & Sediment	50	2.5"	20"	39°F - 113°F

Misc. Accessories		
Webb #	Mfr. #	Description
1115094	PROORNGSTD	O-Ring for Standard Housings
1115093	PROWRENCHSTD	Wrench for Standard Housings
1061937	PROSTDBRK	Bracket for Standard Housings

*Flow rates based on a clean cartridge element and under normal operating conditions, we always recommend a water test to ensure proper performance.

Big 10" Housings & Cartridge Options



125 psi - 8.6 BAR
pH: 6.5 - 9.5
Heavy duty 100% reinforced Polypropylene



Big 10" Housings							
Webb #	Mfr. #	Material	Flow Rate*	Connection	Cartridge Diameter	Cartridge Length	Working Temperature
1280334	PROBCD1B-10	100% PET, FDA Grade Clear Sump	Up to 20GPM 1-4 Bathrooms	1" Lead Free Brass FNPT	4.5"	10"	39°F - 113°F
1196227	PROBIGCLR1LF-10	100% PET, FDA Grade Clear Sump	Up to 20GPM 1-4 Bathrooms	1" Lead Free Brass FNPT	4.5"	10"	39°F - 113°F
1061948	PROBIGCLR1-10	100% PET, FDA Grade Clear Sump	Up to 20GPM 1-4 Bathrooms	1" FNPT	4.5"	10"	39°F - 113°F
1280332	PROBB1B-10	100% PET, FDA Grade Blue Sump	Up to 20GPM 1-4 Bathrooms	1" Lead Free Brass FNPT	4.5"	10"	39°F - 113°F
1061947	PROBIGBLU1-10	100% PET, FDA Grade Blue Sump	Up to 20GPM 1-4 Bathrooms	1" FNPT	4.5"	10"	39°F - 113°F



Cartridge Choices							
Webb #	Mfr. #	Material	Treats	Micron	Cartridge Diameter	Cartridge Length	Working Temperature
1115075	PROCRBBIG-10	Activated Carbon	Chlorine, Taste & Odors	5	4.5"	10"	39°F - 125°F
1280341	PROBL5-10	Activated Carbon	Lead Reduction Chlorine, Taste & Odors	0.5	4.5"	10"	39°F - 113°F
1196220	PROSCLBBIG5MIC-10	Melt Blown Polyphosphate	Hard Water Scale Reduction	5	4.5"	10"	39°F - 177°F
480988	PROMLTBBIG5MIC-10	Melt Blown	Particulate & Sediment	5	4.5"	10"	39°F - 176°F
480989	PROMLTBBIG25MIC-10	Melt Blown	Particulate & Sediment	25	4.5"	10"	39°F - 176°F
481000	PROSTGBIG5MIC-10	String Wound	Heavy Particulate & Sediment	5	4.5"	10"	39°F - 113°F
1061916	PROSTGBIG25MIC-10	String Wound	Heavy Particulate & Sediment	25	4.5"	10"	39°F - 113°F
480990	PROSTGBIG50MIC-10	String Wound	Heavy Particulate & Sediment	50	4.5"	10"	39°F - 113°F
1280339	PROBIM-10	PET Canister	Iron & Manganese Reduction	N/A	4.5"	10"	39°F - 113°F



Misc. Accessories		
Webb #	Mfr. #	Description
1196225	PRODRNKIT	Pressure Gauge and Drain Kit for Big Housings
1196228	PROGAKIT	Pressure Gauge Kit for Housings
1115069	PROORNGBIG	O-Ring for Big Housing Kits

Misc. Accessories		
Webb #	Mfr. #	Description
1115066	PROWRENCHBIG	Heavy Duty Wrench for Big Housing Kits
1196223	PROBIGPLBRK	Plastic Bracket for Big Housing
1115099	PROBIGBRK	Steel Bracket for Big Housing

*Flow rates based on a clean cartridge element and under normal operating conditions, we always recommend a water test to ensure proper performance.

Big 20" Housings & Cartridge Options



125 psi – 8.6 BAR
pH: 6.5 – 9.5
Heavy duty 100% reinforced Polypropylene



Big 20" Housings							
Webb #	Mfr. #	Material	Flow Rate*	Connection	Cartridge Diameter	Cartridge Length	Working Temperature
1280336	PROBCT1B-20	100% PET, FDA Grade Clear Sump	Up to 40GPM 1-5 Bathrooms	1" Lead Free Brass FNPT	4.5"	20"	39°F – 113°F
1280335	PROBCD1B-20	100% PET, FDA Grade Clear Sump	Up to 40GPM 1-5 Bathrooms	1" Lead Free Brass FNPT	4.5"	20"	39°F – 113°F
1196219	PROBIGCLR1LF-20	100% PET, FDA Grade Clear Sump	Up to 40GPM 1-5 Bathrooms	1" Lead Free Brass FNPT	4.5"	20"	39°F – 113°F
1061946	PROBIGCLR1-20	100% PET, FDA Grade Clear Sump	Up to 40GPM 1-5 Bathrooms	1" FNPT	4.5"	20"	39°F – 113°F
1280333	PROBB1B-20	100% PET, FDA Grade Blue Sump	Up to 40GPM 1-5 Bathrooms	1" Lead Free Brass FNPT	4.5"	20"	39°F – 113°F
1061949	PROBIGBLU1-20	100% PET, FDA Grade Blue Sump	Up to 40GPM 1-5 Bathrooms	1" FNPT	4.5"	20"	39°F – 113°F



Cartridge Choices							
Webb #	Mfr. #	Material	Treats	Micron	Cartridge Diameter	Cartridge Length	Working Temperature
1061920	PROCRBBIG-20	Activated Carbon	Chlorine, Taste & Odors	5	4.5"	20"	39°F – 125°F
1280342	PROBL5-20	Activated Carbon	Lead, Chlorine, Taste & Odors	0.5	4.5"	20"	39°F – 113°F
1280281	PROBPIM-20	Activated Carbon	PFOA/PFOS Chlorine, Taste & Odors	1	4.5"	20"	39°F – 113°F
1280337	PROBC1M-20	Activated Carbon	Chloramine, Chlorine, Taste & Odors	1	4.5"	20"	39°F – 113°F
1280338	PROBFIM-20	Polypropylene	Flouride Reduction	N/A	4.5"	20"	39°F – 113°F
1196224	PROSCLBBIG5MIC-20	Melt Blown Polyphosphate	Hard Water Scale Reduction	5	4.5"	20"	39°F – 177°F
480991	PROMLTBBIG5MIC-20	Melt Blown	Particulate & Sediment	5	4.5"	20"	39°F – 176°F
480992	PROMLTBBIG25MIC-20	Melt Blown	Particulate & Sediment	25	4.5"	20"	39°F – 176°F
1061858	PROSTGBIG5MIC-20	String Wound	Heavy Particulate & Sediment	5	4.5"	20"	39°F – 113°F
1061944	PROSTGBIG25MIC-20	String Wound	Heavy Particulate & Sediment	25	4.5"	20"	39°F – 113°F
1109873	PROSTGBIG50MIC-20	String Wound	Heavy Particulate & Sediment	50	4.5"	20"	39°F – 113°F
1280340	PROBIM-20	PET Canister	Iron & Manganese Reduction	N/A	4.5"	20"	39°F – 113°F

*Flow rates based on a clean cartridge element and under normal operating conditions, we always recommend a water test to ensure proper performance.

Big 20" Housings & Cartridge Options



125 psi – 8.6 BAR
pH: 6.5 – 9.5
Heavy duty 100% reinforced Polypropylene



Accessories		
Webb #	Mfr. #	Description
1196228	PROGAKIT	Pressure Gauge Kit for Standard Housings
1196225	PRODRNKIT	Pressure Gauge and Drain Kit for Big Housings
1115069	PROORNGBIG	O-Ring for Big Housing Kits
1115066	PROWRENCHBIG	Heavy Duty Wrench for Big Housing Kits
1196223	PROBIGPLBRK	Plastic Bracket for Big Housing
1115099	PROBIGBRK	Steel Bracket for Big Housing

Reverse Osmosis Kit & Replacement Cartridges



Reverse Osmosis Kit							
Webb #	Mfr. #	Finish	Flow Rate*	Efficiency	Filtration	Connection	Working Temperature
1280278	PRORO	Brushed Nickel Faucet	0.5GPM – 14.8GPD	3:1 Ratio	4 Stage	1/4" CTS Quick Connect	40°F – 100°F



Replacement Cartridges		
Webb #	Mfr. #	Description
1280280	PROROSVCKIT	3 Cartridge Service Kit
1280279	PROROMEMBRANE	1 Membrane Cartridge

*Flow rates based on a clean cartridge element and under normal operating conditions, we always recommend a water test to ensure proper performance.