QUIET-ONE 2000 Kickspace Heaters

ACCESSORIES

EFFECTIVE DECEMBER 1, 2004

QFHK-8 The Quick Fit Hose Kit_____



The concept behind this accessory was that a homeowner who has spent a lot of money on kitchen or bathroom cabinets just doesn't want an installer cutting them up more than is necessary. The Quick Fit Hose Kit provides a means of installing any Quiet-One kickspace heater without having to cut out an access panel in the bottom of the cabinet; it makes Quiet-One kickspace units easier to install as all solder work can be done and all tube connections can be made before the installer slides the Quiet-One into its final resting place under the cabinet; and imagine that, in the unlikely event that service is required, the installer can now pull the kickspace out into the middle of the floor rather than climb into the cabinet.

Each fully packaged kit includes 8' of Watts Radiant synthetic hose with DIN standard oxygen barrier, $\frac{3}{4}$ " radiant underfloor tubing; four $\frac{3}{4}$ " barb x $\frac{1}{2}$ " sweat tees, four $\frac{3}{4}$ " self tite

clamps, and one tube of barb tite glue.

Grilles



Several overlay grilles and replacement grilles are available to enable the contractor's customer to readily match the decor of their house.

All kickspace heater models have grilles available in brown, white, chrome and gold. If other colors are required, the white grille can be painted on site to match any decorator's taste.

MODEL	DESCRIPTION	PART #	FITS THIS KICKSPACE
OLG1-B	Brown Overlay	S10030	KS2004
OLG1-W	White Overlay	S10031	KS2004
OLG1-C	Chrome Overlay	S10039	KS2004
OLG1-G	Gold Overlay	S10040	KS2004
OLG3-B	Brown Replacement	01-0019	KS2006, KS2008
OLG3-W	White Replacement	01-0035	KS2006, KS2008
OLG3-C	Chrome Replacement	01-0036	KS2006, KS2008
OLG3-G	Gold Replacement	01-0037	KS2006, KS2008
OLG4-B	Brown Replacement	01-0022	KS2010
OLG4-W	White Replacement	01-0030	KS2010
OLG4-C	Chrome Replacement	01-0032	KS2010
OLG4-G	Gold Replacement	01-0033	KS2010

Aquastat Kit

The kit is packaged complete with the aquastat, two wires with stripped ends, two wire nuts, and instructions.

MODEL	DESCRIPTION
LTCK 47 100°F-120°F	Kit form of the low temperature cut off (aquastat) which closes on a rise to 120°F and opens on a drop to 100°F.

Note: The aquastat closes on a temperature rise and opens on temperature drop to the lower temperature rating shown.





CATALOG QOACC2004